

NEXUS STEAM 110cm Available in Dual Fuel & Induction*



Choose your colour

*Available at a later date



5 YEAR WARRANTY



Specifications - Nexus Steam

| | NEXUS SO 110 DUAL FUEL (STEAM) | NEXUS SO 110 INDUCTION (STEAM)* |
|--|--|--------------------------------------|
| IODEL NUMBER | NEX110SODF+ COLOUR | NEX110SOEI+ COLOUR |
| VIDTH (MM) | 1092 | 1100 |
| DEPTH EX INC HANDLES (MM) | 604 648 | 604 648 |
| EIGHT - UP TO HOTPLATE (MM) | 905 930 | 905 930 |
| OB RATINGS - KW ELECTRIC, MJ GAS | 1 X 3.8 -15.2MJ« | 3 X 1.85 - 2.50KW |
| | 1 X 3.0 -12.3MJ | 1 X 1.85 - 3.20KW |
| | 2 X 1.55 - 6.2MJ | 1 X 1.15 - 2.00KW |
| | 1 X 0.82 - 3.7MJ | - |
| RIDGING ZONE | NO | YES |
| ERAMIC BURNER (MULTI ZONE) WITH GRIDDLE | 2 X 1.10KW | NO |
| DTAL MJ RATING ** | 43.6MJ | N/A |
| ATED CONNECTED LOAD (KW) @230V | 6.95 | 13.55 |
| ATED CONNECTED LOAD (AMPS) @230V | 31 | 60 |
| ECTRICAL CONNECTION (AMPS) # | N/A | #40 |
| | N/A | #4U |
| HREE-PHASE CONNECTION (AMPS). DNSULT WITH A LICENSED ELECTRICIAN. | 3 X 16A | 3 X 20A |
| /EN CAPACITY LITRES LH RH > | 79 35 | 79 35 |
| /EN TEMPERATURE | 80°C – 240°C (LH) 40°C - 100°C (RH) | 80°C – 240°C (LH) 40°C - 100°C (RH) |
| ELESCOPIC SHELVES SUITS BOTH OR LH OVEN | INCLUDED LH | INCLUDED LH |
| /EN FUEL LH RH | ELECTRIC ELECTRIC | ELECTRIC ELECTRIC |
| /EN TYPE LH RH | MULTI FUNCTION STEAM | MULTI FUNCTION STEAM |
| TERNAL OVEN CAVITY WXDXH (MM) - LEFT | 466 X 385 X 438 | 466 X 385 X 438 |
| TERNAL OVEN CAVITY WXDXH (MM) - ELFT | 400 × 363 × 438 | 400 × 365 × 436 420 × 365 × 225 |
| PARATE GRILL | - | |
| RILL FUEL | DELUXE GLIDE-OUT | |
| KILL FUEL | | ELECTRIC |
| RIDDLE | SUPPLIED MULTI-ZONE GRIDDLE FOR CERAMIC BURNERS, OPTIONAL TEPPANYAKI & SIT-ON GRIDDLE | SUPPLIED INDUCTION GRIDDLE |
| OK CRADLE | SUPPLIED | N/A |
| IST IRON PAN SUPPORTS | YES | N/A |
| AME FAILURE SAFETY DEVICE | YES | N/A |
| ECTRONIC IGNITION | UNDER KNOB | N/A |
| N DETECTOR | N/A | YES |
| | | YES |
| | N/A | |
| DW TEMPERATURE SETTINGS (HOB) | N/A | 3 |
| HILD LOCK (HOB CTRLS) | N/A | YES |
| ROGRAMMABLE CLOCK & CHILD LOCK (OVEN CTRLS) | YES (LH) | YES (LH) |
| INUTE MINDER | YES | YES |
| DOR OPENING LH RH | SIDE DROP DOWN | SIDE DROP DOWN |
| OOR TYPE LH RH | PORTHOLE PORTHOLE | PORTHOLE PORTHOLE |
| /EN LIGHT | X2 | X2 |
| ITALYIC LINERS | SIDES (LH) | SIDES (LH) |
| READ PROVING & STORAGE DRAWER | YES | YES |
| OR GLAZING | TRIPLE | TRIPLE |
| EN FUNCTIONS | | |
| ASE HEAT | YES | YES |
| DNVENTIONAL OVEN | YES | YES |
| FROST | YES | YES |
| LICATE | YES | YES |
| SCALE (STEAM OVEN) | YES | YES |
| JO | YES | YES |
| O MODE | YES | YES |
| N ASSISTED | YES | YES |
| NNED GRILLING | YES | YES |
| N OVEN | YES | YES |
| ILL (STEAM OVEN) | YES | YES |
| PID RESPONSE | YES | YES |
| EAM (STEM OVEN) | YES | YES |
| AILABLE COLOURS | TES | TED |
| | | |
| | YES | YES |
| AINLESS STEEL | YES | YES |
| ATE | YES | YES |
| DRY | YES | YES |
| TTINGS | SATIN CHROME | SATIN CHROME |
| EIGHT | 134.2KG | 139.46KG |
| | | |



*Available at a later date

KEY: ^ Adjustable height, LH Left hand oven, RH Right hand oven, ** Incl. oven where applicable, « Multi ring wok burner, > Litres based on European Standards | Measurements, #Using assessed maximum demand. Not all zones can be used at once. Consult with a licensed electrician.