

DBI253IB.BS

General description

Turbo Drying™ - Fan assisted moist air extraction
Classic
Installation type: Built under work top
Size: XL, 82 cm
Number of baskets: 3
15 place settings
8 Steel™ Construction, SCS+ (Super Cleaning System+)
Top cutlery tray: Top Tray with Instant Lift™; Top Tray with Instant Lift™; Rack for knives (top); Rack for bowls (top); Telescopic rails for top tray; Handle (top)
Upper rack type: Premium - two foldable wine shelves, fixed pin rows and one foldable glass support
Lower rack type: Premium - foldable pin rows

Construction & Performance

Exterior float
8 Steel™ construction
Hidden heater
SCS+ (Super Cleaning System+)
Number of spray arms: 3
Number of spray zones: 9

Use & Flexibility

Number of place settings: 15 place settings
Number of baskets: 3
Top cutlery tray: Top Tray with Instant Lift™; Top Tray with Instant Lift™; Rack for knives (top); Rack for bowls (top); Telescopic rails for top tray; Handle (top)
Upper rack type: Premium - two foldable wine shelves, fixed pin rows and one foldable glass support
Easy sliding telescope rails with ball bearings for the upper basket
Lower rack type: Premium - foldable pin rows
Dense basket wiring in both upper and lower basket
Required inlet water pressure: 0,03-1 MPa

Interaction & Control

Display type: LCD display
Customizable programs: Program memory
Number of programs: 7

Programs, options and modes

7 programmes: Quick wash; Intensive programme; Eco wash; Hygiene wash; Time program; Heavy wash; Rinse and hold
Delayed start: Variable start delay up to 24 hours
Multi tablet function
Super rinse
Time set
Speed mode
Night mode
Extra dry
High temperature
Super rinse

Design & Integration

From front adjustable rear foot
Water connection: Size: 3/4" Can be connected to hot or cold water
Depth (incl. wall spacing): 560 mm
Height setting: 50 mm
Kick plate adjustable depth: 30-94 mm

Safety & Maintenance

Aqua Safe™
Kid Safe™ - panel
Rinse-aid indication: Notification in display

Technical data

Size: 3/4" Can be connected to hot or cold water
Max. temperature of inflow water: 70 °C
Noise level: 44 dB(A)re 1 pW
Reference program: 1
Total cycle time of reference program (min): 169 min
Estimated yearly energy consumption: 295 kWh
Energy consumption reference program: 0,78 kWh
Energy stars: 3,5
Water stars: 5
Water consumption: 12,2 l
Consumption in off mode: 0,5 W
Consumption in standby mode: 2 W
Connection rating: 2000 W
Voltage: 220-240 V
Current: 10 amp
Frequency: 50 Hz
Required inlet water pressure: 0,03-1 MPa
Net weight: 50 kg

Dimensions

Width: 596 mm
Height: 819 mm
Depth: 559 mm
Length electrical cord: 1825 mm
Depth with door open: 1198 mm
Length inlet hose: 163 mm
Length outlet hose: 200 mm

Logistic information

Packaging width: 640 mm
Packaging height: 890 mm
Packaging depth: 680 mm
Gross weight: 53,3 kg
Product code: 732488
EAN code: 3838782326851